

NOTES:

- 1) All resistors are 1%, 1/10W, 0603 unless otherwise specified.
- 2) All capacitors are 0.1uF, 10%, 16V, 0603 unless otherwise specified.
- 3) U1 LGA: Populate C2 and C4.
U2 Socket: Populate C3 and C5; mounted on solder copper side.
- 4) U2 socket: Loranger, 03742 171 6218B.
- 5) Supported devices: KX_IK, KX_KK, KX_NL

COMPANY: **Kionix Inc.**

TITLE: **KX__K/KX_NL Evaluation Board**

DRAWN: Bob Ross	DATED: 4/20/12
CHECKED:	DATED:
QUALITY CONTROL:	DATED:
RELEASED:	DATED:

CODE: DWG794	SIZE: B	DRAWING NO: KAMMDM001R55	REV: 0
SCALE: NONE			SHEET: 1 OF 2

A

A

6

5

4

3

2

1

REVISION RECORD					CHECKED BY:	DATE:
DATE:	DRAWN BY:	DESCRIPTION:				
4/20/12	Bob Ross	Initial release.				

D

D


C

C

B

B

A



COMPANY: **Kionix Inc.**

TITLE: **KX__K/KX_NL Evaluation Board**

DRAWN: Bob Ross	DATED: 4/20/12	CODE: DWG794	SIZE: B	DRAWING NO: KAMMDM001R55	REV: 0
CHECKED:	DATED:	SCALE: NONE		SHEET: 2 OF 2	
QUALITY CONTROL:	DATED:				
RELEASED:	DATED:				